



Double Acting Hollow Plunger Cylinders Çift Etkili Delikli Silindirler

700 bar**24-200 tons****40-250 mm stroke**

- » Double acting type.
- » Hollow plungers for lifting, pushing and pulling applications.
- » Quick and easy coupling with its fast coupler.
- » Acrylic undercoating and top coating against corrosion.
- » Optional hardened solid saddle.
- » Changable saddles with high strength steel against wear.
- » Çift etkili olarak üretilmektedir.
- » Kaldırma, gerdirme ve çekirme uygulamalarında kullanılmak üzere delikli olarak tasarlanmıştır.
- » Hızlı birleştirme kaplini ile hortum montajı seri ve rahat bir şekilde yapılabilmektedir.
- » Paslanmaya dayanıklı akrilik astar ve son kat boya uygulanmaktadır.
- » Opsiyonel sertleştirilmiş dolu başlık sayesinde çift etkili silindir olarak kullanma imkanı sağlanmaktadır.
- » Aşınmaya dayanıklı, yüksek mukavemetli çelik malzemeden yapılan değiştirilebilir başlıklar; milin zarar görmesini önlemekte ve silindirin ömrünü uzatmaktadır.



Hardened / Sertleştirilmiş



Optional Solid Saddle
Opsiyonel Dolu Başlık



Standard Hollow Saddle
Standart Delikli Başlık



Technical Data / Teknik Bilgi

Type Tip	Capacity Kapasite	Stroke Strok (A)	Rod Diameter Rot Çapı (B)	Inside Diameter İç Çap (C)	Outside Diameter Dış Çap (D)	Closed Height Kapalı Boy (E)	Hole Diameter Delik Çapı (F)	Effective Area Etkin Yüzey Alanı	Oil Volume Yağ Hacmi	Weight Ağırlık
	(t)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)			
HCD-024150	24	150	60	80	110	255	30	34	510	16,0
HCD-024250		250				355			850	21,0
HCD-043050	43	50	90	110	145	235	40	62	310	24,0
HCD-043100		100				285			620	28,0
HCD-043150		150				335			930	32,0
HCD-060080	60	80	95	125	165	265	54	84	672	35,0
HCD-060150		150				335			1260	43,0
HCD-060250		250				435			2100	55,0
HCD-100040	100	40	130	170	220	225	80	149	596	48,0
HCD-100075		75				260			1118	60,0
HCD-100150		150				335			2235	75,0
HCD-100250		250				460			3725	100,0
HCD-155100	155	100	160	200	265	275	80	219	2190	95,0
HCD-155150		150				325			3285	110,0
HCD-200150	200	150	180	240	320	360	110	287	4305	175,0

Special production is carried out for every capacity and stroke according to the customer specifications.
Müşteri talepleri doğrultusunda her türlü kapasite ve strokta özel üretim gerçekleştirilmektedir.

