



Flat Type Low Profile Cylinders Düz Kenarlı Yatık Silindirler

700 bar

11-160 tons

6-17 mm stroke

- » Single acting load return type.
- » Suitable for applications required short stroke and precise lifting.
- » Easy usage in narrow places with their low profiles.
- » Quick and easy coupling with its fast coupler.
- » Changable saddles with high strength steel against wear.
- » Black nitrate coating resistive to corrosion.
- » Tek etkili, yük geri dönüşlü olarak imal edilmektedir.
- » Kısa mesafeli ve hassas kaldırma ihtiyacı bulunan uygulamalarda kullanılmak üzere tasarlanmıştır.
- » Düşük profilleri sayesinde dar alanlarda kolaylıkla kullanılabilir.
- » Hızlı birleştirme kaplini ile hortum montajı seri ve rahat bir şekilde yapılabilmektedir.
- » Aşınmaya dayanıklı, yüksek mukavemetli çelik malzemeden yapılan değiştirilebilir başlıklar; milin zarar görmesini önlemekte ve silindirin ömrünü uzatmaktadır.
- » Paslanmaya dayanıklı siyah nitrat kaplama uygulanmaktadır.





Technical Data / Teknik Bilgi

Type Tip	Capacity Kapasite	Stroke Strok (A)	Rod Diameter Rot Çapı (B)	Inside Diameter İç Çap (C)	Outside Diameter Dış Çap (D)	Closed Height Kapalı Boy (E)	Effective Area Etkin Yüzey Alanı	Oil Volume Yağ Hacmi	Weight Ağırlık
	(t)	(mm)	(mm)	(mm)	(mm)	(mm)	(cm ²)	(cm ³)	(kg)
LPS-011006	11	6	40	45	82	35	16	10	1,5
LPS-011011		11				43		17	1,8
LPS-016011	16	11	45	55	92	47	24	26	2,4
LPS-023011	23	11	57	65	102	50	33	36	3,0
LPS-030014	30	14	60	75	115	60	44	62	4,5
LPS-055015	55	15	80	100	140	66	79	118	7,5
LPS-080015	80	15	100	120	165	76	113	170	12,0
LPS-105017	105	17	115	140	190	86	154	262	17,0
LPS-160017	160	17	140	170	245	100	227	386	33,0

Special production is carried out for every capacity and stroke according to the customer specifications.
Müşteri talepleri doğrultusunda her türlü kapasite ve strokta özel üretim gerçekleştirilmektedir.

